

Product Data

Castrol Agri Trans Plus 10W-30

Universal transmission fluid UTTO

Description

Castrol Agri Trans Plus 10W-30 can be used in hydraulic, transmission and PTO of tractors and off-highway equipment. It gives highest levels of wear prevention from start up and throughout the operative period with enhanced corrosion protection properties.

Advantages

- Excellent wet clutches and wet brake performance
- · One oil reduces inventory, simplifies serviceing, avoids misapplication and saves money
- Longer component life reduces downtime and maintenance costs
- Maintains operating temperature and smoother gear changing
- Excellent oxidation stability and anti corrosion properties

Typical Characteristics

| Name | Method | Units | Agri Trans Plus 10W-30 |
|------------------------------|--------------|------------|------------------------|
| Density @ 15C, Relative | ASTM D1298 | g/ml | 0.884 |
| Viscosity, Kinematic 40C | ASTM D445 | mm²/s | 55 |
| Viscosity, Kinematic 100C | ASTM D445 | mm²/s | 9.8 |
| Viscosity Index | ASTM D2270 | None | 161 |
| Viscosity, CCS -25C | ASTM D5293 | mPa.s (cP) | 6900 |
| Viscosity, Brookfield @ -35C | ASTM D2983 | mPa.s (cP) | 35000 |
| Pour Point | DIN-ISO 3016 | °C | -45 |
| Flash Point, COC | ASTM D92 | °C | 232 |

Product Performance Claims

API GL-4
Meets Ford ESN-M2C-134D
MF - M1135, M1143
Volvo 97303:44 (WB 101)
ZF - TE-ML 03E, 05F, 17E, 21F
John Deere J20C
Can be used where Case MS 1207
1209, MAT 3505 & MAT 3525 are specified

Castrol Agri Trans Plus 10W-30 02 Feb 2015 Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com